

Operating Instructions



Robotic Pool Cleaner BASIC 1

Operating Instructions

Contents

- 1. INTRODUCTION2
- 2. SPECIFICATIONS2
- 3. WARNINGS AND CAUTIONS.....2
 - 3.1. Warnings.....2
 - 3.2. Cautions.....2
- 4. POOL CLEANER PARTS.....3
- 5. USING THE POOL CLEANER.....4
 - 5.1. Setup.....4
 - 5.2. Putting the Pool Cleaner into the pool.....4
 - 5.3. Removing the Pool Cleaner from the pool.....5
 - 5.4. Maintenance.....6
 - 5.4.1. Cleaning the filtration system.....6
 - 5.4.2. Cleaning the impeller.....8
 - 5.5. Off-season storage9

Robotic Pool Cleaner BASIC 1

Operating Instructions

1. INTRODUCTION

Thank you for purchasing a Maytronics Pool Cleaner.

We are sure that your Maytronics Robotic Pool Cleaner will provide you with reliable, convenient and cost effective pool cleaning. Its reliable filtration in all pool conditions and all-surface climbing brush enhance maximum pool hygiene.

The Robotic Pool Cleaner by Maytronics deliver advanced cleaning technologies,, long lasting performance and easy maintenance.

2. SPECIFICATIONS

Motor protection: IP 68

Minimum depth: 0.4 m (1.33 ft)

Maximum depth: 5 m (16.4 ft)

Power Supply

Digital "Switch-Mode" Power Supply

- Input - 100 VAC – 250 VAC
- 50 Hz – 60 Hz
- 180 W
- Output - <30 VDC
- IP 54

3. WARNINGS AND CAUTIONS

3.1. Warnings



- Use the originally supplied power supply only
- Ensure the electrical outlet is protected by a ground fault interrupter (GFI) or an earth leakage interrupter (ELI)
- Keep the power supply out of standing water
- Position the power supply at least 3.5 m (12 ft) away from the edge of the pool
- Do not enter the pool while the pool cleaner is working
- Unplug the power supply before servicing
- Keep the Robotic Pool Cleaner out of the reach of children or persons with reduced physical, sensory, or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction.


3.2. Cautions

Use the Pool Cleaner in the following water conditions only:


| | |
|-------------|------------------------------|
| Chlorine | 4 ppm max. |
| pH | 7.0 – 7.8 |
| Temperature | 6 °C – 35 °C (43 °F – 95 °F) |
| NaCl | 5000 ppm max. |

4. POOL CLEANER PARTS

▶ Robotic Pool Cleaner R1




▶ Brushes




PVC Brush
For concrete, PVC,
fiberglass and liner

▶ Filtration



Bottom lid and filter Bag

▶ Power Supply Unit




5. USING THE POOL CLEANER

5.1. Set Up

Position the power supply so that it is approximately in the middle of the long side of the pool at a distance of 3.5 m (12 ft).


Attach the floating cable to the power supply by inserting it with the notch on the connector (1) lined up with the groove in the socket on the power supply and turning clockwise (2).




5.2. Putting the Pool Cleaner into the pool

If Wonder (foam) brush/ Wonder rings are dry, soak them in water until soft.

Shake the Pool Cleaner from side to side or turn it upside down to release trapped air. Let it sink to the pool floor.




Turn the power supply ON.




5.3. Removing the Pool Cleaner from the pool

The Pool Cleaner will perform automatic shut-off at the end of the cleaning cycle.

 Turn OFF and unplug the power supply.



Using the floating cable, bring the Pool Cleaner to the pool's edge.



 DO NOT PULL THE POOL CLEANER FROM THE POOL USING THE CABLE.

5.4. Maintenance




5.4.1. Cleaning the filtration system:

Cleaning the filter bag

 Unplug the power supply.

Turn the Pool Cleaner upside-down.
Open the bottom lid.

Remove the filter bag.



Clean the filter bag with a hose.



We recommend that you periodically wash the filter bag in a washing machine using the gentle cycle program.

Periodically clean the brushes with a hose.

Replacing the filter bag

Put the filter bag over the frame so that the strap is in the middle of the shortest side.

Make sure that filter bag is positioned properly on the frame.





Cleaning the cartridge filters


Note: Don't let the cartridge filters dry out before cleaning.

 Unplug the power supply.

With the pool cleaner upside down open the bottom lid and pull it out.




Open the clips and remove the filters.



Clean the filters with a hose.



Insert the filters with the plastic backing facing out.
Insert the cartridge unit.



5.4.2. Cleaning the impeller


 **Unplug the power supply.**

If you notice debris trapped in the impeller open the impeller and remove the debris.



Cable

To remove the kinks, stretch the cable out completely and let it sit for at least a day in the sun.



5.5. Off-season storage

If the pool cleaner will not be in use for an extended period, perform the following storage steps:

- Make sure that no water is left in the pool cleaner.
- Thoroughly clean the filter bag or cartridge and insert in place.
- Roll up the cable so that it has no kinks.
- Store the Pool Cleaner in a protected area upsidedown (not on its brushes).

